



D210 Mobile Payment Terminal

- **Contactless, Chip, Magstripe**
- **3G, GPRS, Bluetooth, WiFi**
- **iOS & Android Compatible**
- **Visa & MasterCard NFC**
- **PCI PTS 4.x Certified**
- **Apple MFi Approved**

PAX's D210 is a compact mobile payment device designed to interact with customers. Supporting Bluetooth, WiFi, GPRS, 3G (WCDMA) or cable connection, the D210 connects to a wide range of existing and new smart devices to keep up with an emerging marketplace. Apple Inc. has given the D210 a special certification called MFi meaning that Apple has tested and approved the D210 to meet the highest performance standards for integration with any iPad or iPhone.

Your Payment Partner of Choice



D210 Mobile Payment Terminal

Features & Benefits



High Reliability & Exceptional Performance

- Smart card, magstripe & contactless enabled
- Stylishly designed for comfort and convenience
- Contactless card reader supporting NFC
 - 2.8 inch colour screen
- Large memory capacity

Unprecedented Security

- PCI PTS 4.x approved
- Secure key embedded area

Perfect Expansibility

- Open and flexible OS for customized value-added services
- Supports WiFi, Bluetooth, GPRS and 3G (WCDMA)

Specifications

Processor

32-bit ARM 11

Memory

192MB (128MB Flash, 64MB SDRAM)
Micro SD (TF card) up to 32GB

Display

2.8 inch TFT color LCD, 320 x 240 pixels
e-signature (optional)

Printer

High-speed thermal printer, speed: 30 lps
Paper roll width / diameter : 58mm / 40mm

Keypad

10 numeric & 8 function keys

Magnetic card reader

Track1 / 2 / 3, Bi-directional

Smart Card Reader

EMV L1 & L2 certified

Contactless Card Reader

MasterCard Contactless & Visa payWave
ISO14443 Type A/B
Mifare®, Felica, NFC

Communication

Bluetooth 4.0 / WiFi / GPRS
3G (WCDMA) (optional)

Card slots

2 SAMs, 1 SIM
or 1 SAM, Dual SIM

Peripheral Ports

1 x Mini USB (OTG), 1 x Mini USB (RS232)
1 x Power port

Security

PCI PTS 4.x certified

Environmental

0°C to 50°C (32°F to 122°F) operating temperature
-20°C to 70°C (-4°F to 158°F) storage temperature
10% to 93% relative humidity, non-condensing

Voltage

Battery, 7.4V, 2300mAh
Input: 100 - 240V AC, 50 / 60 Hz, 0.3A
Output: 9VDC, 1A

Physical

Length: 162.5mm
Width: 80mm
Height: 56mm

Weight

360g with battery

Accessories

Adapter
Charging Base (optional)

Certifications

PCI PTS 4.x, SRED
EMV Contact L1 & L2
EMV Contactless L1
Visa payWave
MasterCard Contactless
AMEX Expresspay
Discover D-PAS
MasterCard TQM

www.pax.com.cn

This document is provided to you for informational purposes only. All features and specifications are subject to change without notice.
PAX are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries.
All other trademarks or brand names are the properties of their respective holders. Copyright 2015, PAX Technology Limited, All Rights Reserved.

TRIINET
Distribuidor República Dominicana
www.triinet.com


PAX
Your Payment Partner of Choice